

**iQ500**  
**iQ 500**  
**island chimney extractor hood**  
**LF98GB542B stainless steel**



The ceiling-mounted island chimney hood is perfect for all kitchen islands.

- ✓ The 800 m<sup>3</sup>/h extraction rate supplies clean air when cooking.
- ✓ The energy-saving LED lighting ensures optimal visibility when cooking.
- ✓ When required the intensive setting temporarily increases the extraction rate, with automatic revert after 6 min.

#### Features

##### Technical Data

Color chimney : Stainless steel  
 Typology : Chimney  
 Approval certificates : CE, VDE  
 Length electrical supply cord (cm) : 130  
 Height of the chimney (mm) : 699-879/699-999  
 Height of product, without chimney (mm) : 52  
 Minimum distance above an electric hob : 550  
 Minimum distance above a gas hob : 650  
 Net weight (kg) : 29.0  
 Type of control : Electronic  
 Number of speed settings : 3-stage + 2 intensive  
 Maximum output air extraction (m<sup>3</sup>/h) : 440  
 Boost position output recirculating (m<sup>3</sup>/h) : 360  
 Maximum output recirculating air (m<sup>3</sup>/h) : 290  
 Boost position air extraction (m<sup>3</sup>/h) : 800  
 Number of lights : 4  
 Diameter of air outlet (mm) : 150 / 120  
 Grease filter material : Washable synthetic  
 Connection Rating (W) : 172  
 Current (A) : 10  
 Voltage (V) : 220-240  
 Frequency (Hz) : 50; 60  
 Plug type : GB plug  
 Installation typology : Island



#### Optional accessories

LZ53650     Recirculating kit

**iQ500**  
**iQ 500**  
**island chimney extractor hood**  
**LF98GB542B stainless steel**

#### Features

##### Design

- 90 cm wide
- Soft touch button control for extractor speeds and light
- White electronic display
- Stainless steel hood with glass canopy
- Height adjustable chimney sections
- For ceiling mounted installation

##### Key features

- Electronic control
- Electronic power level display
- LED lights
- SoftLight with dimmer function
- 1 x metal grease filter cassette
- Steel filter cover
- Soft touch button control with 7-segment display
- Grease and charcoal filter saturation indicators

##### Performance/technical information

- Suitable for ducted and re-circulating operation
- Extraction rate according to EN 61591 ø 15 cm:  
max. Normal use 440 m³/h  
Intensive 800 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at  
maximum normal setting: extraction rate: 58 dB (A) re 1pW (44 dB  
(A) re 20 µPa sound pressure)
- 3 power levels and 2 intensive settings
- Automatic intensive revert
- Adjustable automatic after running

**iQ500**  
**iQ 500**  
**island chimney extractor hood**  
**LF98GB542B stainless steel**

Dimensioned drawings

